

Introducing **AURA** Thermal Receipt Printer Series



**Fast.
Quiet.
Reliable.**

- ✓ 180mm/sec high-speed printer with 2MB flash memory
- ✓ Guillotine type auto cutter
- ✓ Clam-shell, drop and load design for easy paper loading and print head cleaning
- ✓ Light weight, quiet and compact
- ✓ Supports bar code printing, international character sets and other optional languages

POSIFLEX™
committed to your security

www.posiflexusa.com

tel: (510) 429-7097

sales@posiflexusa.com

AURA 7000

Including a “clam shell, drop-and-use” design that the point-of-sale industry has grown accustomed to this quiet high-speed and high-resolution with auto-cut thermal receipt printer is lightweight, compact and optimized to deliver the best possible combination of image quality and speed. It supports multiple interfaces, bar-code printing, international character sets and other optional languages, as well as selectable dot fonts. The AURA also supports extended print modes, such as multiple width/height, reverse and line/page printing. With 2MB of flash memory, the built-in character registration allows users to store or download special character patterns or graphic logos. An anti-static enclosures added reliability.

Technical Specifications

Printer

| | |
|------------------------|---|
| Print Method | Thermal Sensitive Line Dot Method |
| Print Speed | 180mm/sec (Approx. 56 lines/sec) |
| Print Resolution | 8 dots/mm and 512 dots/line (576 dots/line max.) |
| Print Font | 9 x 16 / 12 x 24 dot |
| Character size | 1.1 x 2.0 / 1.5 x 3.0mm |
| Character set | 95 Alphanumeric, 59 International, 128 x 8 Graphic English, Simple / Traditional Chinese, Japanese Kanji, Katakana, Portuguese, Canadian-French, Nordic, Cyrillic, Euro Dollar Sign |
| Bar Code | UPC-A/E, EAN13/8, ITF, CODE39/93/128, CODABAR |
| Characters per inch | 22.6 CPI / 16.9 CPI |
| Interfaces | Serial (RS232) and Parallel (Centronics) auto-interface sensor with appropriate interface cable |
| Data Buffer | 10 KB |
| Auto Cutter Type | Guillotine |
| Auto Cutter Capability | Partial cut (1 point at center left) |
| Power | 24 VDC \pm 5% |
| Power Consumption | Approx. 1.5A max. @ 115V AC 50 ~ 60 Hz |
| Reliability | MTBF – 30,000 hours Print-head Life: 100km Auto-Cutter: 500,000 cuts min. |
| Printer Drivers | Win 9x, Win NT/2000/XP, OLE POS (OPOS) |
| User Memory | 2MB Flash memory |
| Paper Feed Method | Friction Auto-Feed |
| Paper Load Method | Drop-and-Use |
| Dimensions | 148mm (W) x 199mm (D) x 144mm (H) |
| Weight | 1.35kg net |
| Color | Beige or Charcoal |

Paper

| | |
|----------------------|---------------------------------|
| Type | Thermal Roll Paper |
| Paper Roll Formation | External side is heat sensitive |
| Dimensions | 79 to 80mm (W) x diameter 83mm |
| Thickness | 60-80 um |

Options

Wall-mount bracket / Space Pole for saving counter space

Specifications are subject to change without notice.

POSIFLEX™
Committed To Your Security

www.posiflexusa.com

sales.department@posiflexusa.com