

SigLite LCD 1x5



Models: T-L460-HSB-R
T-L460-B-R
T-LBK460-HSB-R
T-LBK460-BSB-R
T-LBK460-B-R

The SigLite®LCD 1X5 is an advanced biometric electronic signature pad with backlit transfective LCD that displays “electronic ink” under the pen tip during signing. Bundled secure software APIs provide for interactive text, graphics, and pen-tap hotspots and checkboxes which enable users to navigate screens, read agreements, and select preferred options before signing. Interfaces include Topaz - HSB® secure HID, - BSB™ (virtual serial USB) and - B serial interface. Backlit transfective LBK460 models are provided in addition to non-backlit L460.

Sensor Type	Touch-screen
Pen Type	Rugged patented passive, battery-less pen
Dimensions	6" x 3.8" x 1.4" 152 x 95 x 36 mm
Signing Area	4.4" x 1.3" 112 x 33 mm
Data Conversion Rate	377 Points per second.
Signature Resolution	410 points per inch (programmable to 3280 dpi)
Data Interface	-HSB (HID/USB), -BSB (Virtual serial/USB) -B (serial).
Software Support	SigPlus development tools for ActiveX, .NET, C++, Native Java, Multi-browser, Word, Excel, Acrobat, pDoc Signer, eSign Emcee server, etc. Updates and support at no charge.
Authentication	Forensic-quality .SIG data capable of examination and authentication with Topaz SigCompare™ & SigAnalyze® software.
Warranty	2-Year Limited Warranty, with renewal option.
Patents	http://www.topazsystems.com/Information/legal.htm#patents

Bundled Software

Developer's Tools

Active X
Java
C++
.NET

Plug-Ins

MS Word , Excel
Adobe Acrobat
pDoc™ Signer App for PDFs

Server / Browser Tools

Topaz eSign Emcee®
SigPlusWeb™

Applications & Utilities

SigTool Imager Plus

Verification

SigCompare™
SigAnalyze®