



Zebra DS6700 Series

Handheld digital imager scanner

Capture data and images with single multi-use device

The versatile DS6700 Series delivers the functionality of a 1-D and 2-D bar code scanner, digital camera and document scanner in a single device. Designed to meet a wide variety of business needs across a variety of industries, the DS6700 enhances employee productivity and streamlines business processes in retail, government, manufacturing and more by combining an onboard 1.3 megapixel camera with high performance scanning features and superior digital imaging technology.

Enhance employee productivity

The DS6700 Series delivers the accurate and rapid first time scanning of bar codes required to maximize employee productivity. Whether you need to read 1-D, 2-D or PDF417 bar codes, the DS6700 Series provides true point-and-shoot bar code capture ' there is no need to orient products to the scanner window, and a viewfinder ensures the image is properly captured the first time. Users can dynamically switch between hands-free and handheld operation to quickly, easily and safely scan large items. And a pick list function expands usability from the front room to the back room, enabling rapid processing of orders and more.

Superior document clarity for record-keeping applications

Our text enhancement software delivers the document clarity required to streamline record-keeping, replacing paper-based files with electronic filing. From medication prescriptions to bills of lading, the high-resolution camera and text-enhancing software work hand-in-hand to ensure the visibility of text on documents captured, including very small print. As a result, critical business information is literally at your fingertips, helping to reduce administrative and regulatory compliance costs.

An outstanding return on investment

The DS6700 Series reduces capital and operating expenses by eliminating the need to purchase, manage and support additional devices ' such as digital cameras and separate bar code scanners for different symbologies. Fewer devices to deploy significantly reduces the time and costs associated with training ' and positively impacts productivity. The ability to remotely track, deploy and upgrade DS6700 Series scanners reduce typical management costs. And since even the most intelligent devices require a support plan, Zebra's Service from the Start Advance Exchange Support agreement provides next-business-day delivery of a replacement device for maximum uptime and true service peace of mind.

For more information on how the DS6700 series can give your enterprise a business advantage, visit www.zebra.com/ds6700 or access our global contact directory at www.zebra.com/contact

FEATURES

1.3 Megapixel imaging

Provides resolution to support image capture and bar code scanning; provides flexibility to capture documents as large as 8.5 in . x 11 in./ 21.6cm x 27.9cm

Support for all major 1-D, PDF, postal and 2-D symbologies

Delivers application flexibility ; eliminates need for multiple devices ' and associated costs

RSM (Remote Scanner Management) Ready

Lowers IT expenses and TCO by enabling remote management from a central location

Text enhancement technology

Ensures legibility of text in scanned documents

6 ft./1.8m drop specification, tempered glass exit window

Designed to endure the rigors of everyday use for maximum reliability and uptimes; reduces downtime and TCO

Multiple on-board interfaces; universal cable compatible

Easy to install; futureproof ' today's cradle can connect to tomorrow's host

360° omni-directional scanning; wide working range, laser aiming pattern

PHYSICAL CHARACTERISTICS

| | |
|----------------------|--|
| Dimensions: | 6.55 in. H x 4.72 in. L x 2.82 in. W 16.6 cm H x 11.9 cm L x 7.1 cm W |
| Weight: | 6.4 oz. (182 g) |
| Voltage and Current: | 5 +/-10%VDC @ 350 mA |
| Color: | Cash Register White (shown) or Twilight Black |

PERFORMANCE CHARACTERISTICS

| | |
|--|--|
| Light Source: | Aiming: 650 nm laser diode Illumination: 630 nm LED |
| Field of View: (Vertical x Horizontal) | SR - Standard range: 34° V x 43° H DC - Document capture: 35° V x 44° H |
| Roll / Pitch / Yaw: | SR - Standard range: 360°, ±65°, ± 60° DC - Document capture: 360°, ±65 °, ±60° |

SYMBOLGY DECODE CAPABILITY

| | |
|---------------------------|---|
| 1-D: | UPC/EAN and with supplementals, Code 39, Code 39 Full ASCII, Tri-optic Code 39, RSS variants, UCC/EAN 128, Code 128, Code 128 Full ASCII, Code 93, Codabar (NW1), Interleaved 2 of 5, Discrete 2 of 5, MSI, Codell, IATA, Bookland EAN, Code 32 |
| PDF417 (and Variants): | PDF417, microPDF417 and composite codes |
| Postal: | U.S. Postnet and Planet, U.K., Japan, Australian, and Dutch |
| 2-D: | MaxiCode, DataMatrix (ECC 200), QR Code and Aztec |

Print Contrast: 25% minimum reflectance

Motion Tolerances: Horizontal velocity: 5 in. (12.7 cm)
per second

Interfaces
Supported: **DS6707:** RS-232C (Standard,
Nixdorf, ICL, and Fujitsu);
USB (Standard, IBM SurePOS,
Macintosh)

DS6708: Includes above plus IBM
468x/469x, keyboard
wedge and Synapse connectivity.

Note: National Drug Codes (NDC) can be encoded in
various symbologies. The DS6708-DL
can be programmed to parse these codes using
Advanced Data Formatting (ADF) rules.

USER ENVIRONMENT

| | |
|---------------------------|---|
| Sealing: | IP41 (Water and Dust Resistant) |
| Operating Temperature: | 32° to 122° F / 0° to 50° C |
| Storage Temperature: | -40° to 158° F / -40° to 70° C |
| Humidity: | 5% to 95%, non-condensing |
| Drop Specifications: | Withstands multiple 6 ft. (1.8m) drops to concrete |

Ambient Light
Immunity: Immune to normal artificial indoor
and natural outdoor
(direct sunlight) lighting.

REGULATORY

| | |
|--------------------|--|
| Electrical Safety: | UL6950-1, CSA C22.2 No. 60950- 1, EN60950-1 / IEC60950-1 |
| Laser Safety: | EN60825-1:1994 +A1: 2002 +A2 : 2001, IEC60825-1, 21CFR1040.10 and 21CFR1040.11, CDRH Class II, IEC Class 2 |

EMI/RFI: FCC Part 15 Class B, ICES-003
Class B, CISPR 22, CISPR 24;
Medical electrical equipment:
EN60601-1-2: 2002

Environmental: Compliant with RoHS directive
2002/95/EEC

Mounting Options
(Accessories) Intellistand with adjustable height:
5'10 in. (12.7'25.4 cm) and
adjustable angle: 0°90°
Desktop and wall-mount holders
are also available.

Power Supplies: Power supplies are available for
applications that don't supply
power over the host cable.

WARRANTY

Subject to the terms of Zebra's hardware warranty
statement, the DS6707/8 handheld scanner products are
warranted against defects in workmanship and materials
for a period of five years from the date of shipment. For
the complete Zebra hardware product warranty
statement, go to: <http://www.zebra.com/warranty>

Easy to use; no need to align
item and scanner; virtually
no training required

Optional hands-free Intellistand

Enables presentation
scanning and automatic
switching between
hands-free and handheld
modes

IMAGING CHARACTERISTICS (DS6707 ONLY)

Image (Pixels): 1.3 Megapixel: 1280 pixels H x 1024 pixels V

Graphics Format Support: Images can be exported as Bitmap, Jpeg, and Tiff

Image Transfer Speed: USB 1.1: Up to 12 Megabits/second
RS232: Up to 115 kb baud rate

Image Transfer Time : Typical USB application is ~ 0.2 seconds with a compressed Jpeg of 100 kb

Imaging Distance: (Vertical x Horizontal)

Document Sizes: Minimum Distance (Approximate)

| | |
|----------------------------------|--------------------|
| 2 1/8 x 3 3/8 in. (5.4 x 8.6 cm) | 2.4 in. (6.1 cm) |
| 4 x 6 in. (10.2 x 15.2 cm) | 5.7 in. (14.5 cm) |
| 5 x 7 in. (12.7 x 17.8 cm) | 6.9 in. (17.5 cm) |
| 8 x 11 in. (21.6 x 28 cm) | 11.9 in. (30.2 cm) |

Ranges are from the nose of the scanner and are based on DC ' Document Capture focus only.

*Note: Imaging characteristics only apply to the DS6707. The DS6708 does not support image transfer

SR - STANDARD RANGE FOCUS

| LABEL DENSITY | DEPTH OF FIELD | |
|------------------------|----------------|---------------|
| | DS6700 | |
| | ENGLISH | METRIC |
| 5 mil (Code 39): | 1.1 ' 6.5 in. | 2.8 ' 16.5 cm |
| 13 mil (100% UPC/EAN): | 0.5 ' 9.7 in. | 1.3 ' 24.6 cm |
| 20 mil (Code 39): | 0.5 ' 15.2 in. | 1.3 ' 38.6 cm |
| PDF417 (10 Mil): | 0.9 ' 7 in. | 2.3 ' 17.8 cm |
| Datamatrix (10 Mil): | 1.1 ' 7.5 in. | 2.8 ' 19.1 cm |

DC ' DOCUMENT CAPTURE FOCUS

| LABEL DENSITY | DEPTH OF FIELD | |
|------------------------|----------------|---------------|
| | DS6700 | |
| | ENGLISH | METRIC |
| 5 mil (Code 39): | 2.5 ' 10 in. | 6.5 ' 25.4 cm |
| 13 mil (100% UPC/EAN): | 0.8 ' 16.8 in. | 2 ' 42.7 cm |
| 20 mil (Code 39): | 0.7 ' 28.3 in. | 1.8 ' 71 cm |
| PDF417 (10 Mil): | 1.9 ' 11.8 in. | 4.8 ' 30 cm |

Datamatrix (10 Mil):

2.6 ' 12.2 in.

6.6 ' 31 cm



ZEBRA

Part number SS-DS6700. Printed in USA 04/15.©2015 ZIH Corp. ZEBRA, the Zebra head graphic and Zebra Technologies logo are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All rights reserved. All other trademarks are the property of their respective owners.

ZEBRA TECHNOLOGIES